

Digital temperature display

Minimum/maximum
temperature memory

Key switch

Forced-air cooling

Visual and audible alarm
signal, even in the case
of power failure

5 drawers

Comfortable access

Automatic fast defrosting

Connection for
forwarding alarms and
for PC-supported
temperature
documentation

Condensate evaporation

FROSTER-BL-530



Flexible interior design

We deliver our devices in any combination with shelves and / or drawers.



Optimized air guide plate

The optimized air guide plate reduces temperature deviations inside the system to a minimum.

FROSTER-

BL-530/-730 according to DIN 58375



- **External housing** made from galvanised sheet steel (rust-proof), with white, anti-scratch powder coating. Length of the plug cable: approx. 3 m.
- **Adjustable feet** to compensate for uneven floors.
- **Interior** made from smooth aluminium with colourless protective coating. Gibs (every 15 mm) for flexible interior arrangement.
- **Interior consists** of five drawers of aluminium, height adjustable on telescopic runners with stops, stacking height: 23 cm. Capacity per drawer: FROSTER-BL-530 app. 64 plasma cartons, FROSTER-BL-730 app. 96 plasma cartons, each 19 x 13 x 2,5 cm, each 400 ml size.
- **Extra-thick 70-mm insulation**, made from high-quality, compression-moulded and environmentally friendly material. Energy saving.
- **Self-closing door** with easy-to-replace plastic magnetic seal frame, lockable.
- **Door stop** on the right-hand side (by default, see illustration), or the left-hand side, can be retrofitted.
- **Forced-air cooling** with axial blower, switches off automatically when you open the door, ensures a uniform temperature and minimizes temperature deviations.
- **Automatic fast defrosting** thanks to time-limited and temperature-monitored reversal of the refrigerant circuit.
- **Condensate evaporates** in stainless steel heated dish beneath the refrigerator floor.
- **Key switch protected control panel against tampering.** Membrane keyboard with digital temperature display and minimum/maximum temperature memory.
- **Warning functions** with visual and audible alarm signal in the case of power failure and temperature deviations. In the case of power failure, the monitoring unit remains in operation for approx. 72 hours on battery power. Door open alarm after 60 seconds.
- **Alarms** can be forwarded using the potential-free contact (e.g., to a mobile phone with optional GSM-Module or to a control centre).
- **RS485 interface** for connecting to PC-supported temperature documentation (using the optional KIRSCH-PC-KIT).
- **Ventilation-enforced refrigerating machine**, vibration free, hermetically sealed, energy saving, low-noise, easy to service. Inlet air and exhaust air flow through the ventilation slits at the front.

Specification

	FROSTER-BL-530	FROSTER-BL-730
Capacity	500 litres	700 litres
Temperature setting	-32 °C	-32 °C
Voltage	220 – 240 V, 50 Hz	220 – 240 V, 50 Hz
Power consumption	730 Watt	730 Watt
Normal consumption	9,8 kWh/24 h	11,4 kWh/24 h
Admissible ambient temperature	from +10 °C to +32 °C	from +10 °C to +32 °C
Heat emission (max.)	913 Watt	913 Watt
Exterior dimensions (including door handle and distance from wall)	w x d x h = 77 x 76 x 193 - 196 cm	w x d x h = 77 x 98 x 193 - 196 cm
Interior dimensions	w x d x h = 62 x 56 x 140 cm*	w x d x h = 62 x 77 x 140 cm*
Exterior dimensions with door open at 90°	w x d = 77 x 144 cm	w x d = 77 x 166 cm
Drawer inner dimensions	w x d x h = 56 x 39 x 10 cm	w x d x h = 56 x 60 x 10 cm
Max. load drawer	50 kg	50 kg
Weight	Net weight 159 kg, gross weight 189 kg	Net weight 199 kg, gross weight 234 kg

*usable width 2 cm, usable depth 11 cm, usable height 13 cm less

Optional equipment

- **LED illumination** mounted on side wall.
- **Equipped with castors.**
- **Cooling machine** with cold water connection.
- **Outer housing** in stainless steel 4301, longitudinal brushed.
- **Additional drawer** made aluminium.
- **Drawers insert** (set) with 4 adjustable length and 25 (FROSTER-BL-530) or 40 (FROSTER-BL-730) cross dividers per drawer.
- **Additional length and cross dividers.**
- **Drawer** made of stainless steel, also possible with cover plate, black colored, instead of aluminum.
- **Shelf** 59.7 x 45 cm on rails or overlays.
- **Baskets** on rails 60 x 45 x 10 cm.
- **Aluminium** tray with rails 60 x 40 x 2,5 cm.
- **GSM-Module** for alarm text message transmission.
- **Temperature documentation:**
 - PC-KIT-NET, PC-KIT-USB-MONITORING or PC-KIT-STICK including software for temperature documentation.
 - 4-pin PT 100 or PT 1000 temperature sensor, class 1/3 B, including built-in reference body.
 - Disc-type pen recording thermometer, with 7-day measuring cycle, incorporated, with 100 recording discs and 5 felt tip pens.
 - Mechanical pen-recording thermometer with two waxed paper strips.